



**WACKER
NEUSON**
all it takes!



Zero Tail tracked excavator EZ36

1000368069

[Home](#) >> [Catalog](#) >> [Products](#) >> [Excavators](#) >> [Tracked Excavators](#) >> [Tracked Zero Tail Excavators](#) >> **Zero Tail tracked excavator EZ36**



Zero Tail tracked excavator EZ36

Material number 1000368069

High thermal resistance: 100% performance at up to 45 degrees ambient temperature

Product details

- Hydraulically controlled drive pedals for precise driving without using hands
- High thermal resistance: 100% performance at up to 45 degrees ambient temperature
- Increased stability due to the externally guided rollers and optional additional rear weight
- Spacious comfort cab with clearly arranged operator's controls
- Zero Tail: No tail swing, can turn 360° when up against walls

General

- Shipping weight: 3,344 - 4,260 kg
- Width / height / transport length: 1,750 / 2,491 / 5,503 mm
- 300 mm rubber track
- Dozer blade
- Working light mounted to the boom
- Tool kit, including grease gun and operator's manual

Engine

- Water-cooled YANMAR diesel engine, model 3TNV88, 3-cylinder / 1,642 ccm, net output according to ISO 22.2 kW (30.2 hp), rated speed 2,400 rpm (level 3a tier IV-i)
- Auto idling system

Canopy

- Adjustable and suspended comfort seat with mock leather upholstery and safety belt, canopy (and cab) meets the latest ROPS, TOPS and FOPS* provisions

Hydraulics

- Double variable and 2 gear wheel pumps (2 x 40 + 26.3 + 11.3 l/min)
- Summation regulation
- Hydraulic pilot control via joystick
- Valve control according to ISO, DIN, SAE, PCSA and EURO
- Auxiliary hydraulic connections for two directions of movement, mounted on bucket arm
- Auto2 speed gearbox, 2 travel speeds automatically shifted, 2nd gear manually lockable
- Hydraulic damping for drive pedals and throttle
- Hydraulic oil cooler
- Enlarged, pressure-free return line (for various attachments)
- Proportional control for AUX I; adjustable discharge volume via potentiometer

Configuration of Zero Tail tracked excavator EZ36 on 23/07/2020

Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE