



**WACKER  
NEUSON**  
*all it takes!*



## High frequency internal vibrator with integrated converter IRFU38/120/5

5000610099

[Home](#) >> [Catalog](#) >> [Products](#) >> [Concrete Technology](#) >> [Internal Vibrators](#) >> [High Frequency Internal Vibrators with integrated converter](#) >> [High frequency internal vibrator with integrated converter IRFU38/120/5](#)

### High frequency internal vibrator with integrated converter IRFU38/120/5

Material number 5000610099



Electric internal vibrator with integrated frequency inverter for concrete compaction. Protection hose length of 5 meters. With integrated personal protection switch (Bodyguard™).

### Product details

#### High frequency internal vibrator, designed for the toughest application conditions

- Integrated frequency inverter, therefore two pieces of equipment in one for convenient handling and compensation for fluctuating input voltages. No external inverter required.
- Power cable outfitted with Bodyguard™ (shutdown of the equipment in cases of emergency within 3 msec.) to protect the operator from electric shock if the electric power supply is insufficiently secured.
- Complete potted electronic components for a long service life
- Wear resistant vibrator head made of steel, completely induction hardened
- Repairable vibrator head (exchange of individual components)
- Ergonomically shaped switch box
- RPM-stable, powerful electric motor designed, developed and produced in-house - Made in Germany
- With integrated thermal overload protection breaker
- Power cable made of sturdy, flexible rubber

### Comes with

- Internal vibrator
- Operator's manual

## Technical specifications

### High frequency internal vibrator with integrated converter IRFU38/120/5

#### ELECTRICAL - OUTPUT DETAILS

Nominal current	7,00 A
Nominal voltage	110 - 130 V
Nominal frequency	50 - 60 Hz
Nominal power [P]	0,65 KW
Phase	1 ~

#### ELECTRICAL SYSTEM

Breaker Switch On/Off	yes
Integrated transformer	yes
Light cone	15,0 m
Length Cable	15,00 m
Kind of plug	CEE-Plug 2P+E 16A 110V 4H

#### ENVIRONMENT DATA

Protection class	I / Protective earthing
Storage temperature range	-20 - 60 °C
Degree of protection	IP67
Sound level LpA	79,0 dB(A)
Measuring method LpA	LPA1m
Sound level LpA (Standard)	DIN EN ISO 11201
Operating temperature range	-10 - 40 °C
Vibration total value ahv	2,5 m/s <sup>2</sup>
Vibration value ahv (Standard)	DIN EN ISO 20643
Uncertainty in measurement HAV	0,5 m/s <sup>2</sup>

#### MECHANICAL - OUTPUT DETAILS

Amplitude at air	1,90 mm
Vibrations	12.000 1/min
Vibrations (Hz)	200 Hz

## MOTOR

Motor type	asynchronous motor
------------	--------------------

## OPERATING FLUIDS

Oil volume	0,010 l
------------	---------

Oil specification	Klüberoil 4UH1-46N
-------------------	--------------------

## THERMAL - OUTPUT DETAILS

Overheat limit activation	150 °C
---------------------------	--------

## MECHANICAL DETAILS

Length Hose	5,00 m
-------------	--------

Length Head	345 mm
-------------	--------

External diameter hose	31 mm
------------------------	-------

Head diameter/-diagonal	38 mm
-------------------------	-------

Head design	round
-------------	-------

Weight	13,60 kg
--------	----------

Rubber cap	no
------------	----

## Custom Attributes

Model serie	IRFU
-------------	------

Product line	Premium
--------------	---------

### Please Note

This product availability can vary from country to country. It is possible that information / products may not be available in your country. More detailed information on engine power can be found in the operator's manual; the started power may vary due to specific operating conditions Subject to alterations and errors expected. Applicable also to illustrations.

Copyright © 2018 Wacker Neuson SE