



SUPRA

ENGINE

Make	: PERKINS
Type	: 1204F-E44TAN Diesel Engine
Number of Cylinders	: 4 in line
Bore & Stroke	: ø 105 x 127 mm
Displacement	: 4400 cc
Maximum Power	: 99,8 HP (74,4 kW) @2200 rpm
Maximum Torque	: 450 Nm @1400 rpm
High power and torque output, water cooled turbocharged diesel engine.	
Compatible with U.S EPA Tier 4 Final and EU Stage IV exhaust gas emission regulations	

TRANSMISSION

- Autoshift transmission for heavy duty service
- 6 forward, 3 reverse gears
- Torque convertor lock (Lock-Up)
- Torque converter with 2,38:1 stall ratio
- Electrically controlled 2 Wheel drive or 4 Wheel Drive selection
- Transmission oil cooler
- A neutral circuit allows starting only when the control lever is in neutral position for safety.

AXLES

- Heavy duty service type ZF axles
- Planetary outboard type reduction gears
- Total 16 degrees oscillation on the front axle
- Equipped with LSD (Limited Slip Differential) optional diffrentail lock for rear axle

CAB & HOOD

- Widened visual angle
- Ergonomic & Aesthetic Interior Design
- 3" LCD display on front panel and 5,5" coloured TFT display on side panel
- Opera Control System
- High capacity A/C system
- Cool-box
- Improved ventilating with 15 air nozzles
- ISO Patternshifter
- ROPS and FOPS certificated cab
- Air suspension seat
- TIPSHIFT front loader joystick
- Pool type floor mats
- Removable lids
- Smart-Link
- Storage boxes for operator
- Foldable side steps
- Plastic fuel tank
- LED working ligths
- LED step ligths

HYDRAULIC SYSTEM

Closed type hydraulic system with variable displacement piston type pump, renewable flowsharing and valves with regeneration (Flowcharging)	
Main Pump Flow	: 163 L/min @2200 rpm
Pressure	: 250 bar

DRIVING SPEED

@ 2200 rpm engine speed	
1 st gear	: 6 km/h
2 nd gear	: 9 km/h
3 rd gear	: 12 km/h
4 th gear	: 20 km/h
5 th gear	: 28 km/h
6 th gear	: 40 km/h



FILLING CAPACITIES

Engine Oil Pump	: 8,8	L
Engine Cooling System	: 22	L
Fuel Tank	: 150	L
Hydraulic Oil Tank	: 70	L
Transmission Oil	: 16	L
Front Axle Differential	: 9	L
Front Axle Hub Reducers	: 0,85 x 2	L
Rear Axle Differential	: 18	L
Ad Blue	: 19	L

TIRES




Front	: 16/70 - 20 12 Ply Rating
Rear	: 16,9 - 28 14 Ply Rating (Optional : 18,4- 26 14 Ply Rating)

OPERATING WEIGHT

Operating weight (with standard equipment)	: 9.500 kg
--	------------

Operational weight, complying with the ISO 6016 standards, includes full fuel tank, hydraulic system and other liquids, 75 kg operator weight and standard equipped machine weight. Optional equipments are not included.




HMK102B SUPRA





LOADER PERFORMANCE	
6 in 1 bucket capacity	1,1 m ³
Max. bucket breakout force	7930 kgf
Max. loading arm breakout force	7166 kgf
Lifting capacity to maximum height	3561 kg

BACKHOE PERFORMANCE	Telescopic Arm (extended)	Telescopic Arm (retracted)
	Bucket capacity	0,17 m ³
Max. bucket breakout force	7240 kgf	7240 kgf
Max. dipper breakout force	2536 kgf	3300 kgf







Standart Accessories



Optional Accessories



Optional Attachments



HIDROMEK®

FACTORY - HEAD OFFICE
Ahi Evran OSB Mahallesi Osmanlı Caddesi No:1 06935 Sincan / ANKARA / TURKEY
Tel: (+90) 312 267 12 60 Fax: (+90) 312 267 12 39
www.hidromek.com

Notice:
Hidromek has the right to modify the specifications and design of the model indicated on this brochure without prior notice.